

Filters & Filter/Regulators

- Light weight acetal body with polyamide bowl
- Filter/Regulator with glass face chrome gauge
- Low pressure drop
- Semi-automatic drain with manual override
- Filter with adjustable 0-120 PSI regulator
- Can be wall mounted or panel nut mounted



Lubricators

- Light weight acetal body with polyamide bowl
- Siphon tube filter provides clean lubricant down stream
- Adjustable oil feed with tamper-proofing capability
- Can be filled while under pressure



Order Guide

Filters

Model Number*	Port Size (in.)	Flow Capacity (SCFM)	Maximum Supply Pressure (PSIG)	Maximum Operating Temp. (°F)	Filter Capacity	Dimensions Height x Width x Depth (in.)	Mod Kit
RT-F250	¼"	30	230	120	5 micron	5.75 x 1.65 x 1.65	MOD250
RT-F380	⅜"	80	180	120	5 micron	6.85 x 2.49 x 2.05	MOD375
RT-F500	½"	80	180	120	5 micron	8.03 x 2.95 x 2.49	MOD500

Filter/Regulators

RT-FR250-G	¼"	30	230	120	5 micron	7.80 x 1.65 x 1.65	MOD250
RT-FR380-G	⅜"	80	180	120	5 micron	9.41 x 2.49 x 2.05	MOD375
RT-FR500-G	½"	80	180	120	5 micron	10.87 x 2.95 x 2.49	MOD500

Lubricators

L250	¼"	30	230	120	42	6.18 x 1.65 x 1.65	--
L380	⅜"	80	180	120	68	7.95 x 2.05 x 2.49	--
L500	½"	80	180	120	140	8.94 x 2.49 x 2.95	--

* To order Filter/Regulator without gauge, substitute "0" for "G" in model number.

Accessories & Replacement Parts

Filters

Part Number	Replacement Element	Replacement Gauge	Bowl Assy	O-Ring	Mounting Bracket (Optional)
RT-F250	F250-E	--	F250-BMD	F250-OR	F250-BKT
RT-F380	F380-E	--	F380-BMD	F380-OR	F380-BKT
RT-F500	F500-E	--	F500-BMD	F500-OR	F500-BKT

Filter/Regulators

RT-FR250-G	FR250-E	PG-160-1.5CB	F250-BMD	F250-OR	F250-BKT
RT-FR380-G	FR380-E	PG-160-1.5CB	F380-BMD	F380-OR	F380-BKT
RT-FR500-G	FR500-E	PG-160-1.5CB	F500-BMD	F500-OR	F500-BKT

