
Rescue

Concentrated Compressor Cleaner

Rescue consists of premium, fast-acting concentrate cleaners. It is designed to be added to compressor lubricants to remove carbon, varnish and other hydrocarbon-related deposits.

Rescue is recommended for use at a ratio of 1 part concentrate to 10 parts lubricant.

Instructions:

1. Determine the amount of Rescue required for the compressor.
2. Drain a volume of oil from the compressor equal to the volume of Rescue being added.
3. Add Rescue to the lubricant sump of the compressor up to recommended concentration.
4. Operate the compressor as normal for 24-72 hours. Monitor filters for clogging; replace as required.
5. If the compressor is shut down at any time during the cleaning period, ensure it is run for at least 30 minutes prior to draining the lubricant-cleaner mixture.
6. Drain the lubricant-cleaner mixture from the compressor while the oil is still hot. You get the most effective drain when the oil is not allowed to cool and settle.
7. Refill the compressor with a high-quality, synthetic lubricant.

ATTRIBUTES

- Outstanding carbon and varnish removal
- Fast-acting
- Non-toxic/non-hazardous

TYPICAL LUBRICANT PROPERTIES

Rescue Grades	15
Viscosity cSt @ 40°C	15
Viscosity cSt @ 100°C	2.9
Flash Point °F (°C)	180 (82)