

39 cfm Gas/Diesel Engine Driven Rotary Screw

39 cfm @ 150 psi

Features

- Airend manufactured with German rotary screw components
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Industrial-duty drive engine
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- UL control components

Platinum Compressor Features

- Air/oil cooler
- Battery mounted and wired
- SIMPLEX controls
- Tank discharge ball valve
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada

Platinum Stainless Features

- All Platinum features
- First oil and filter change
- Stainless steel 12 inch install line
- Stainless steel discharge lines
- Tank discharge ball valve



Model	HP	Mount	Tank	Drive engine	Length	Width	Height
R18DEK30	17	Tank mount	30 Gallon Horizontal	Kohler Diesel	48	30	48
R18GEH30	18	Tank mount	30 Gallon Horizontal	Honda Gas	48	30	48
R18GEK30	18	Tank mount	30 Gallon Horizontal	Kohler Gas	48	30	48

Add -P to model number to make Platinum Unit. Unit does not come standard with a fuel tank.

No Start Up Kit Required ■ Optional 5-year Pump Warranty Available

Industrial Gold

Quality Air Compressors at a Great Price.

industrialgold.com ■ 1-800-531-9656 ■ Fax 972-352-6364

© Industrial Gold 2-2019

