

Base Plate Mounted Compressors

- Powder coated, extra heavy steel base plate
- Large canister intake filter with replaceable filter elements
- Pressure relief safety valve
- Pressure gauge



K5HGA-B



T25KGB-B

Gas

- Constant run control set at 105-125 PSI (single stage) or 145-175 PSI (two stage)
- High quality pilot valve
- Pneumatic throttle idle control
- Honda GX Series OHV Engine or Kohler OHV V-Twin Engine



GT11HGB-B

Single Stage

Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
K5HGA-B	K	5.5	Recoil	1285	14.2	8.6
GC8HGA-B	GC	8	Start	890	24.6	16.0
GC11HGA-B		11	Electric	1070	28.6	18.3
J11HGA-B	J		Start	865	31.8	20.9

125 PSI

Two Stage

Model	Pump	HP	Drive	Pump RPM	CFM Disp	Del'd Air
GT5HGB-B	GT	5.5	Recoil	570	14.2	9.1
GT8HGB-B		8	Start	820	24.6	15.4
GT11HGB-B		11	Electric	985	28.6	16.3
W11HGB-B	W	760		24.1	17.6	
U18HGB-B	U	800		49.8	34.7	
T25KGB-B	T	25		625	86.4	67.3

175 PSI

Options

Oil sight glass

Air line filter ■ Lubricator

Electric start

Other pressures available upon request

Other engine options available upon request