

DATA SHEET




U 4.630

ROTARY VANE– VACUUM PUMPS

oil-lubricated
air-cooled

MAKE IT BECKER.





1 Vacuum connection (G3)

2 Exhaust air connection (G4)

3 Oil filler cap

4 Oil sight glass

5 Screw plug for oil drain

6 Rubber buffer position

7 PT100

- incl. non-return valve and oil separator

- The motor illustration may vary

- Dimensions in inch


	Nominal capacity		Vacuum		Emission sound pressure level ¹⁾		Weight w/o motor lbs	Oil ²⁾ U.S. gal.
	CFM 50 Hz	CFM 60 Hz	Torr 50 Hz	Torr 60 Hz	dB(A) 50 Hz	dB(A) 60 Hz		
U 4.630 SA/K	366	430	2.25	2.25	80	83	816	3.7
U 4.630 F/K	366	430	0.375	0.375	80	83	816	3.7

¹⁾ DIN EN ISO 3744 (KpA = 3 dB(A)) interval of 39.4 inch, at medium load, both connection sides piped

²⁾ Becker Synthetic Oil, Becker Premium Synthetic Oil (PAO) and Becker Food Grade Vacuum Pump Oil

3~ Motors													L
#	50 Hz				60 Hz				Version		Weight		
	hp	V	rpm	A	hp	V	rpm	A		lbs	inch		
01	20.1	Δ400	IE3	985	33.4	24.1	Δ460 Δ400	IE3	1183	33.7	UL (E235514) • CSA CC329B IP 55 • ISO F • bimetal	432.2	60.9
02						24.1	YY230/Y460 YY208	IE3	1183	69.1/34.6	UL (E235514) • CSA CC329B IP 55 • ISO F • bimetal	358.3	60.9
03	20.1	Δ200/Y350	IE3	987	68.6/39.6	24.1	Δ200/Y380–400 Δ200/Y350	IE3	1185	69.7/40.2–39.6	UL (E235514) • CSA CC329B IP 55 • ISO F • bimetal	359.4	60.9
04						24.1	Δ400/Y490	IE3	1185	38.9/22.4	UL (E235514) • CSA CC329B IP 55 • ISO F • bimetal	434.4	60.9


▪ Type plate data on current consumption and rotation speed of the motors may vary. Tolerance -1.5/+2% in each case.



Suction air rate refers to the intake pressure
Reference data (atmosphere): 0 In. HgV / 760 Torr, 68°F; Tolerance: $\pm 5\%$

ACCESSORIES

- Gas ballast valve ST 626-0-4 (no. 76870499626)
- Temperature trigger unit for monitoring the pump temperature with the use of the integrated temperature sensor PT100¹⁾
- Temperature monitor TW for monitoring the oil temperature¹⁾
- Oil level switch ST 682-0-2 for monitoring the oil level¹⁾
- Oil bath heating and thermostat
- Maintenance indicator ST 691-0-1 for oil separating elements (no. 91680099691)
- Oil-to-water heat exchanger
- External suction filter, e.g. FV 540¹⁾
- Oil: Becker Lube M100 mineral, S100 synthetic and SL100 food



Temperature trigger unit



Temperature monitor TW



Oil level switch ST 682-0-2



Maintenance indicator ST 691-0-1



Example for an external suction filter

¹⁾ See separate data sheet
▪ Combination options on request

MAKE IT BECKER.