



HAZARDOUS LOCATION IA COMPRESSORS

Here at Central Air Equipment, we have a variety of reciprocating compressor models for hazardous locations to service the energy industry ranging from ¾ HP up to 7.5 HP as a standard. If you require more air, we can supply custom compressors as well as rotary screw air compressors if you require continuous air demand. See below for the Standard Models:

CAE-HL-SR/ SWT-12G-.75HP

¾ HP Class 1 Division 1 or 2
120V/230V/1PH or 230V/460V/3PH
Base mount or 12 Gallon Horizontal
Single stage - max 125psig

CAE-HL-SR/ SWT-30G/60G-2HP

2 HP Class 1 Division 1 or 2
120V/230V/1PH or 230V/460V/3PH
Base mount or 30/60 Gallon Vertical
Single stage - max 125psig

CAE-HL-SR/ SWT-30G/60G-3HP

3 HP Class 1 Division 1 or 2
120V/230V/1PH or 230V/460V/3PH
Base mount or 30/60 Gallon Vertical
Single stage - max 125psig

CAE-HL-SR/ SWT-80G-5HP

5 HP Class 1 Division 1 or 2
230V/1PH or 230V/460V/3PH
Base mount or 80 Gallon Vertical
Two-stage - max 175psig

CAE-HL-SR/ SWT-80G-7.5HP

7.5 HP Class 1 Division 1 or 2
230V/460V/3PH
Base mount or 80 Gallon Vertical
Two-stage - max 175psig

FS Curtis • Fu Sheng • Trident • SPX-Hankison • Super-Dry

centrairequipment.com | info@cae-ltd.ca | 1.888.893.4667



OPTIONAL AIR DRYERS



**SUPERDRY
AIR DRYER**

-40 Dewpoint
No moving parts
No Electrical Required
No Purge Air Loss



**MEMBRANE
AIR DRYER**

-40 Dewpoint
No moving parts
No Electrical Required



**HEATLESS REGENERATIVE
TWIN TOWER**

-40 Dewpoint
120V 1PH powered

All models easy to service and available with CRN.

**Ask your CAE representative to help recommend the best option
for all technical, budgetary and maintenance requirements**

FS Curtis • Fu Sheng • Trident • SPX-Hankison • Super-Dry

centrairequipment.com | info@cae-ltd.ca | 1.888.893.4667