

# 45 cfm Hydraulic Driven Rotary Screw Compressor



45 cfm @ 100 psi

40 cfm @ 150 psi

## Features

- All hydraulic fluid and air connections on same side
- ASME/CRN certified safety valves
- CAS SMART fluid control system
- Compressor load/unload operation
- Easy to remove compressor cover
- External NEMA 4 on/off switch
- Heavy-duty industrial rotary screw airend
- Hydraulic fluid flow regulator
- Hydraulic fluid pressure regulator
- Hydraulic fluid bypass valve
- Intake filter silencer
- NEMA 4 load/unload switch
- Steel mounting plate
- Vibration mounting pads
- 12 volt compressor air & oil cooler pack\*
- 12 volt control system\*\*



Scan this QR code to learn more about this product

## Package Options

- Cold weather heating package
- Cover color change
- High ambient temperature cooling package
- Hose reels
- Hydraulic fluid cooler
- Tank mounted
- 24 volt operation
- 110 volt operation

\* Cooler pack to be mounted external to compressor system. 12 volt control voltage connection to be supplied by vehicle/equipment compressor is mounted to.

Do not let hydraulic fluid exceed 190 F°



Model	cfm @ 100 psi	cfm @ 150 psi	Hydraulic psi Required	GPM Hydraulic Flow Required	Length	Width	Height
H-BM40RS	45	40	2250	14	30	20	25

Dimensions are representatives of package dimensions not total space required for mounting.

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2024

