

	Model Informa	ition		
Model	PK			
Model HP	5			
Starting Method	Fixed Speed			
Cooling	Air Cooled			
Pressure	115	125	150	175
General Data				
ACFM 3¢	20	19	18	16
ACFM 1¢	19	18	16	14
Full load pressure (psig)	115	125	150	175
Package kW at rated pressure	5	5.1	5.3	5.6
Specific power (kW/100 cfm)	25.0	26.8	29.4	35.0
Unloaded power (kW)	1.8			
Control type	Load / Unload			
Starter Type	Full voltage			
	Air End Dat	:a		
Air end model	SKY-40 ENCAPSULATED			
Number of Thrust bearings (M/F)	2/2			
Drive Type	Belt			
	Cooling Data (	Air)		
Ambient temperature rating (°F min/max)	33° / 104°			
Heat rejected (BTU/HR)	15661			
Max. static back pressure	1/4" H <sub>2</sub> O			
Approach temperature (°F)	14° to 90°			
	Sound Leve	el		
Sound level (dBA)			1	
	Electrical Da	ita		
Electrical enclosure rating	Nema 1			
Drive motor insulation class	F			
Drive motor nominal kW	4			
Drive motor nominal speed (rpm)	3450			
Drive motor service factor	1.2			
Drive motor efficiency at 100% (%)	89.7			
Motor enclosure type (drive and fan)	TEFC			
Fan motor nominal kW (A/C)	0.08 kW			
Package FLA @ 208V/60HZ	25			
Package FLA @ 230V/60HZ	23			
Package FLA @ 460V/60HZ	11.5			
Package FLA @ 575V/60HZ	9.2			
Electrical code(s)		UL 5	08A	
	Filtration and Lub	rication		
Air filter micron rating (μm)		<b>3</b> μ <b>m</b>		
Fluid filter micron rating (µm)	β <b>100</b> @ <b>25</b> μm			
Fluid carryover (PPM)	≤5			
Fluid capacity (Gal)	1.7			
Factory fill fluid	KTL-8000	KTL-8000	KTL-8000	KTL-10000
•				



## **PK-5/T**

	<b>Model Information</b>

 $\mathsf{PK}$ Model Model HP 5

**Starting Method** Fixed Speed Cooling Air Cooled

**Pressure** 115 125 150 175

## Package Information

## **Base Mount**

3/4" NPT-Male Discharge connection Condensate connection N/A Dimensions (L X W X H inches) 38 X 23 X 26 3¢ Weight (lbs) 337 348

1¢ Weight (lbs)

**Tank Mount** 

Discharge connection 2" NPT-Female Condensate connection 1/4" NPT - Female Dimensions (L X W X H inches) 65 x 23 x 49 3¢ Weight (lbs) 577

1¢ Weight (lbs)

Tank Mount with Dryer

3/4" NPT-Female Discharge connection Condensate connection Dual 3/8" O.D. Push-to-connect

588

Dimensions (L X W X H inches) 65 x 23 x 49 3¢ Weight (lbs) 657 668

1¢ Weight (lbs)

## **Product Features**

Motor brand WEG Starter brand Siemens Cooling fan type Axial Enclosure Open Standard **Current monitor** Phase monitor Standard in 3¢ Stainless steel **Tubing material**