



## **SULLIVAN'S WEATHER-ALL PORTABLE COMPRESSOR FLUID**

- **Used for all weather conditions**
- **Anti-wear additives**
- **Anti-rust additives**
- **Anti-foaming additives**
- **Quick water separation**
- **Excellent viscosity index**
- **Extended life**



**As of December 2010, we are now using WEATHER-ALL 5W-20 as the standard factory fill in all our portable compressors.**

**5 gallon Pail P/N 00823062 0009**

**55 gal Drum P/N 00823062 0010**



## Product Description

**WEATHER-ALL™ COMPRESSOR FLUID** is designed for all types of rotary screw air compressors used in varying conditions encountered in the construction industry.

Sullivan-Palatek's *Weather-All* is formulated as a 5W-20 Multi-Viscosity fluid with additives for maximum protection against scuffing and wear to bearings and rotors.

Extensive testing has shown this fluid exhibits excellent resistance to foaming, oil oxidation and corrosion.

Special attention has been made toward limiting rust of ferrous metals and corrosion of yellow metals.

## Product Features and Benefits

Our *Weather-All* lubricant will provide extended life compared to other brand oils.

*Weather-All* fluid provides quick water separation which helps protect equipment in wet and humid service environments.

Our compressor fluid has an excellent viscosity index (180), as well as, low pour point (-40°F).

This specially formulated **multi-viscosity** compressor fluid provides wear control for steel and brass parts when operating at maximum pressure ratings, resulting in excellent compressor operation.

*Weather-All Compressor 5W-20 Fluid* combines the superior additive technology and quality hydrocarbon based oils for **Extended Life** and is a custom-formulated lubricant specifically designed for long life under the severe, demanding conditions normally encountered in recirculating systems such as rotary screw compressors.

*Weather-All* combines the advantages of a synthesized hydrocarbon, which results in performance improvements beyond conventional mineral oils and many synthetic oils.

## Characteristics:

- Exceptional oxidative stability
- Low sludging tendency
- Thermal & hydrolytic stability
- Rust and corrosion inhibited
- Lower equipment maintenance
- Longer life
- Low evaporation loss
- Improved performance
- Viscosity stability
- Extended anti-wear protection

Portable Compressor Fluid Multi-Viscosity			
ISO Viscosity Grade	32	Viscosity Index	180
SAE Viscosity Grade	SW-20	Pour Point	-40°C
Viscosity, cSt. 210°F	50 SUS		-40°F
100°F	170 SUS	Flash Point	199°C
Normal Service Life	1000 Hrs		
These values are not intended for use in preparing specifications			